



TRTS 010

ABS plastic without LCD display



TRTS 010 SS

stainless steel enclosure

stainless steel enclosure, vandalism secure version for schools, military barracks and public buildings

Features

- Active transmitters
0-10 Vdc or 4-20 mA output
- 8 different temperature ranges in same unit, selectable via jumpers on pcb

-20°C to +150°C, -50°C to +50°C, -20°C to +80°C, -30°C to +60°C, 0 to +40°C, 0 to +50°C, 0 to +100°C and 0 to +150°C.

other temperature ranges on request
- IP 30
- ABS plastic enclosure or stainless steel enclosure

Application/Description

The room temperature transmitter TRTS have been designed for wall mounting and is used to sense temperature in heating, ventilating and air conditioning systems.

The housing have ventilated openings with connection terminal PCB and temperature sensing element inside the housing.

The unit can be mounted on surface or on a conduit box.

Ordering


Room temperature transmitter

Type no.	Output	Housing	Display
TRTS 010	0-10 Vdc	ABS plastic	No
TRTS 010D	0-10 Vdc	ABS plastic	Yes
TRTS 010SS	0-10 Vdc	stainless steel	No
TRTS 420	4-20 mA	ABS plastic	No
TRTS 420D	4-20 mA	ABS plastic	Yes
TRTS 420SS	4-20 mA	stainless steel	No


Technical data

Measuring ranges	8 different temperature ranges in same unit as standard selectable via jumpers on pcb. with manual zero point correction (+/-10K)
Sensing element	PT1000, DIN EN 60751, class B
Deviation temperature	+/-0.2K at +25°C
Connections	3-wire for 0-10 Vdc 2-wire for 4-20 mA
Power supply	24 Vac/dc +/- 10% for output 0-10 Vdc 15-35 Vdc for output 4-20 mA
Protection type	IP30 (according to EN 60529)
Ambient temperature	-30°C to +70°C
Humidity	< 95% r.H. non-precipitating air
Protection class	III (according to EN 60730)
Standards	CE conformity, electromagnetic compatibility according to EN 61326:2006 according to EMC directive 2004/108/EC
Display	8-digit display, cutout 36x14 mm (W x H), for displaying actual temperature (only for TRTS 010D and TRTS 420D)



Dimensions in mm for ABS plastic enclosure



Dimensions in mm for stainless steel housing



Electrical connections



8 different temperature ranges in same unit, selectable via jumpers on pcb

Measuring ranges (adjustable)	DIP 1	DIP 2	DIP 3
-20 °C ...+ 150 °C	ON	ON	ON
-50 °C ... + 50 °C	OFF	ON	ON
-20 °C ... + 80 °C	ON	OFF	ON
-30 °C ... + 60 °C	OFF	OFF	ON
0 °C ... + 40 °C	ON	ON	OFF
0 °C ... + 50 °C	OFF	ON	OFF
0 °C ...+ 100 °C	ON	OFF	OFF
0 °C ...+ 150 °C	OFF	OFF	OFF

We reserve the right to make changes in our products without any notice which may effect the accuracy of the information contained in this leaflet.