	-	<u>alala</u>	<u>alala</u>
	See O U		
Source States	B SONG	SAPE C Same	ZVOC
SL-C	SL-C	SL-C	Street as
			Sellen I
LOC VIS	NHE ST I		
000		<u>କାକାକ</u>	222
A BILLOW			
51 52	53 51	DC+ DC- INI	IN2 IN3 IN4

4 Channels relay

Model: KW-RL4S

Overview

Relay modules suitable for switching of higher voltages and perfect for use with microcontrollers including Door interface. The relays used are rated up to 10A and have NO/NC contacts. Each channel has an LED indicator to show the relay is on.

Specifications

- Channels: 4, Active by High/Low selectable
- Connects directly to a microcontroller/ Door interface
- LED Indicator for each channel
- Dual Trigger design, using special two-way driver IC design, fly away to ride the world premiere of Electronic Science and Technology
- Anti-jamming capability, using freewheeling diode protection
- Part of the relay contacts using double-sided bold wiring for large current through, safe and reliable.
- Each relay output leads to the normally open and normally closed two electric shock, easy to use and flexible.

Technical Information

- 12VDC Power supply
- Switching Capacity: 10A
- Maximum Voltage: 250VAC / 30VDC
- 4-Channel Dimensions: 73 x 51 x 19mm (L x W x H)



Distribution by **Keyword Technologies & Services Co., ltd.** 19 Soi BangkokNon 9/1 Bang Khen, Muang Nontaburi, Nontaburi, 11000 Thailand +66-81-913-0033