


AUTO-DOOR EQUIPMENT



YAD-141FS

Five-range LCD KEY Switch


Size: 92Lx92Wx46H(mm)
Hole Dimension: 85Lx85Wx43H(mm)
Mechanical working life: over 75000 times
Display Screen: TFT34x25mm



YAD-142FS

M-246 Touch type LCD screen


Size: 86x86(panel)
Screen Dimension: 15x45mm
Screen: 2.8 inches
Static current: (12V)
Power in: DC12-24V
Function: 5 ranges



YAD-143FS

Auto-door remote controller


Size: 123Lx50Wx32H(mm)
Power supply: AC/DC12-36V
The interval time to open lock and auto-door: 0.5S
Professional appliance: Built-in surge absorber
Current of electric lock: 3A(12V)
Action current: 85mA(Non-current electric lock)



YAD-150PS

Automatic door back-up power with lithium battery


Size: 243Lx59Wx45H(mm)
96Lx43Wx55H(mm)
Input Voltage: AC220V, 50Hz
Output Voltage: DC24V, 2.6AH; DC12V, 5.2AH
Working Mode: Automatic working or keep opening
Indicator and Protect: Charging proceeding shown by LED. Low voltage will automatically cut
Charging time: Around 10 hours
Open times: About 550 times



YAD-160ML

Magnetic Lock for Auto-door


Size: 70Lx70Wx58H(mm)
Armature plate: 100Lx53Wx53H(mm)
Holding Force: 70kg(150Lbs)
Voltage: DC12V±10%
Current Draw: DC12V/180mA
Suitable for: Auto-door
Surface Temp: About 50°
Weight: 0.8kg



**YAD-161ML(24V)
YAD-161ML(MF)**

80KG Square Automatic Door Magnetic Lock

Size: 71Lx65Wx45H(mm)
Suction tablets: 60Lx32Wx10H(mm)
Bracket: 147Lx65Wx3H(mm)
Adsorption stent: 116Lx68Wx38H(mm)
Input voltage: AC and DC 12-24V



**YAD-161ML(110V)
YAD-161ML(220V)**

80KG Square Automatic Door Magnetic Lock

Size: 71Lx65Wx45H(mm)
Suction tablets: 60Lx32Wx10H(mm)
Bracket: 147Lx65Wx3H(mm)
Adsorption stent: 116Lx68Wx38H(mm)
Input voltage: 110V/220V

