# ELECTRIC DROP BOLT SERIES



#### Mini Intelligent Electric Bolt

Size: 70.3Lx59WX27.5H(mm)

Voltage: 12V DC
Current: 100mA
Safe feature: NO or NC
Weight: 0.2kg






#### Fail Safe Electric Bolt W / Magnetic Feature

Size: 205Lx35Wx40H(mm)

Voltage: 12V DC

Current: Start 900mA, standby 120mA
Suitable for: Wooden door, glass door,
Metal door, fireproof door

Feature: Fail safe Weight: 0.72kg





## Fail Safe Electric Bolt W / Signal


Size: 205Lx35Wx40H(mm)

Voltage: 12V DC

Current: Start 900mA, standby 110mA
Suitable for: Wooden door, glass door,

Metal door, Fireproof door

Feature: Fail safe
Weight: 0.72kg






#### Fail Safe Electirc Bolt W / Signal & Time

Size: 205Lx35Wx40H(mm)

Voltage: 12V DC

Current: Start 900mA; standby 110mA
Suitable for: Wooden door; glass door;
Metal door; Fireproof door

Feature: Fail safe
Time delay: 0,3,6,9sec
Weight: 0.72kg





#### Fail Safe Electirc Bolt W / Signal, Time & LED


Size: 205Lx35Wx40H(mm)

Voltage: 12V DC

Current: Start 900mA; standby 110mA Suitable for: Wooden door; glass door;

Metal door; Fireproof door

Feature: Fail safe
Time delay: 0,3,6,9sec
Weight: 0.72kg





### Fail Safe Electric Bolt with Signal, Time & LED

Size: 190Lx30Wx39H(mm)

Voltage: 12V DC

Current: Start 850mA; standby 150mA
Suitable for: Wooden door; glass door;
Metal door; Fireproof door

LED: Light on when locked; Light off when unlocked

Signal output: Door status NO/COM

Time delay: 0,3,6,9sec Weight: 0.6kg





### Fail Safe Electric Bolt W/signal, Time, Open Wire(12-24V)

Size: 205Lx35Wx40H(mm)

Voltage: 12V-24V

Current: Start 12V/900mA, standby 100mA

Start 24V/730mA, standby 70mA

Suitable For: Wooden door, glass door, Metal door, fireproof door

Feature: Fail safe
Time delay: 0,3,6,9sec
Weight: 0.74kg

