ELECTRIC DROP BOLT SERIES




Fail Safe Electric Bolt For Auto-door

Size: 205Lx35Wx40H(mm)

Voltage: 12V DC

Current: Start 930mA ,standby 130mA

Suitable for: Auto- door Feature: Fail safe Time delay: 0,3,6,9sec Weight: 0.72kg





Fail Safe Sturdiness Electric Bolt W


Size: 192Lx25Wx37H(mm)

Voltage: 12V DC Current: Start 900mA Stand by: 80mA

LED: Light on when locked; Light off when unlocked Suitable for: Wooden door, glass door,

Wooden door, glass door, Metal door, fireproof door

Feature: Fail safe Induction distance: 8mm Time delay: 0,3,6,9sec Weight: 0.68kg





Fail Secure Sturdiness Electric Bolt

Size: 192Lx25Wx37H(mm)

Voltage: 12V DC Current: Start 900mA Stand by: 80mA

LED: Light on when locked; Light off when unlocked

Suitable for: Wooden door, glass door, Metal door, fireproof door

Feature: Fail secure Induction distance: 8mm Time delay: 0,3,6,9sec Weight: 0.68kg





Fail Secure Sturdiness Electric Bolt with Cylinder

Size: 210Lx25Wx42H(mm)

Bolt: 16mmDIA, stainless steel 13mm throw Voltage: 12V DC (24V DC need order)

Current: Start960mA

Stand by: 130mA


LED: Light on when locked; Light off when unlocked

Suitable for: Wooden door; metal door; fireproof door

Feature: Fail secure

Signal output: Door status output, NC/COM

Time delay: 0,3,6,9sec
Weight: 1.0kg





Fail Safe Electric Bolt for Fully Frameless Glass Door

Size: 150Lx40Wx38H(mm)


Voltage: 12V DC(24V DC need order)

Current: Start 960mA Standby: 130mA

LED: Light on when locked; Light off when unlocked

Signal output: Door status output, NO/COM
Suitable for: 10-12mm frameless glass door

Suitable for: 10-12mm
Feature: Fail safe
Time delay: 0,3,6,9sec
Weight: 1.36kg





Fail Safe Sturdiness Electric Bolt For Narrow Frame Door

 Size:
 150Lx24Wx36H(mm)

 Voltage:
 12V DC(24V DC)

 Current:
 Start 900mA

 Standby:
 130mA

LED: Light on when locked; Light off when unlocked

Feature: Fail safe
Time delay: 0,3,6,9sec
Weight: 1.06kg

