ELECTRIC DROP BOLT SERIES



Fail safe sturdiness electric bolt is for narrow door

185Lx25.7Wx37H(mm) Size:


Voltage: DC12V

Current: Start 960mA; standby 180mA Suitable for: Electric Bolt For Narrow Door

Signal output: Lock signal NO/COM

LED: Light on when locked; Light off when unlocked

Feature: Fail safe Time delay: 0,3,6,9sec Weight: 1.2kg





Fail Safe Electric Bolt W/signal, Time, Open Wire, & Cylinder

270Lx30Wx48H(mm) Size


Voltage: 12V DC

Start 1200mA; standby 200mA Current:

LED: Light on when locked; Light off when unlocked Suitable for: Heavy door; metal door; wooden door

Signal output: Lock signal NO/NC/COM

Feature: Fail safe 0,3,6,9sec Time delay: Weight: 1.6kg





Fail Secure Electric Bolt W/signal, Time, Open Wire, & Cylinder

270Lx30Wx48H(mm) Size:

12V DC Voltage:

Start 1200mA; standby 200mA Current:

LED: Light on when locked; Light off when unlocked Suitable for: Heavy door; metal door; wooden door

Lock signal NO/NC/COM Signal output:

Feature: Fail secure Time delay:

0,3,6,9sec Weight: 1.6kg





Fail Secure Electric Bolt W/signal, Open Wire, & Cylinder(Slope Bolt)

Size: 270Lx30Wx48H(mm)

Voltage: 12V DC

Current: Start 1200mA, standby 200mA


LED: Light on when locked; Light off when unlocked

Suitable for: Heavy door/metal door/wooden door Lock signal NO/NC/COM Signal output:

Feature: Fail secure

Weight:

1.6kg





Fail Secure Electric Bolt W/Cylinder

Size: 150Lx36Wx57H(mm)

Voltage: 12V DC


Current: Start 1000mA, standby 350mA Bolt: 16.5(length)*20(diameter)(mm)

LED: Light on indicates locked, light off indicates unlocked Suitable for: Wooden door, metal door, fireproof door, glass door

Lock signal(NO/NC/COM); Door signal(NO/COM) Signal output: Feature: Fail Secure

DistanceWithin 8mm Induction:

Weight: 1.25kg





Fail Safe Electric Bolt W/signal, Time, Open Wire, & Cylinder

260Lx30Wx73H(mm) Size: 12V DC ± 10% Voltage:

Current: Start 1200mA, standby 200mA

LED: Light on when locked; Light off when unlocked Suitable for: Heavy door, metal door, wooden door

Signal output: Lock signal NO/NC/COM

Fail safe Feature: Time delay: 0,3,6,9sec Weight: 1.8kg

