


BRACKET & INSTALLATION OF ELECTRIC BOLT



YB-630B(LED)

Fail Secure Electric Bolt W/signal, Time, Open Wire, & Cylinder


Size: 260Lx30Wx73H(mm)
 Voltage: 12V DC \pm 10%
 Current: Start 1200mA, standby 200mA
 LED: Light on when locked; Light off when unlocked
 Suitable for: Heavy door, metal door, wooden door
 Signal output: Lock signal NO/NC/COM
 Feature: Fail secure
 Time delay: 0,3,6,9sec
 Weight: 1.8kg



YB-630C(LED)

Fail Secure Electric Bolt W/signal, Open Wire, & Cylinder(Slope Bolt)


Size: 260Lx30Wx73H(mm)
 Voltage: 12V DC \pm 10%
 Current: Start 1200mA, standby 200mA
 LED: Light on when locked; Light off when unlocked
 Suitable for: Heavy door, metal door, wooden door
 Signal output: Lock signal NO/NC/COM
 Feature: Fail secure
 Weight: 1.8kg



YB-660

Fail Secure Electric Bolt W/Cylinder & Handle


Size: 285Lx30Wx40H(mm)
 Voltage: 12V DC
 Current: Start 2000mA, standby 400mA
 Bolt: 20.8(length)*18(diameter)(mm)
 LED: Light on indicates locked, light off indicates unlocked
 Suitable for: Wooden door, metal door, fireproof door, glass door
 Signal output: Lock signal(NO/NC/COM); Door signal(NO/COM)
 Feature: Fail secure
 Weight: 2.0kg



YB-700A/B(LED)

Fail Secure / Fail Safe Electric Bolt W/Signal & Time


Size: 225Lx35Wx38H(mm)
 Voltage: 12V DC
 Current: Start 1200mA; standby 200mA
 LED: Light on when locked; Light off when unlocked
 Suitable for: Heavy door, metal door, wooden door, glass door
 Signal output: Lock signal NO/NC/COM, Door signal NO/COM
 Feature: Fail safe(A) Fail secure(B)
 Time delay: 0,3,6,9sec
 Weight: 1.0kg



YB-800A/B

Fail Secure / Fail Safe Electric Bolt W/Signal & Time

Size: 220Lx34Wx38H(mm)
 Bolt: 16(length) * 16(diameter)(mm)
 Voltage: 12VDC \pm 10 %
 Current: Start 1200mA; standby 200mA
 Signal Output: Door signal NO/COM
 Feature: Fail safe(A) Fail secure(B)
 Suitable For: Wooden door, metal door, fireproof door, glass door
 Material: 304 stainlesssteel, wiredrawing finishing
 Weight: 1.0kg



YB-900A/B

Surface-mounted Electric Bolt W/Cylinder

Size: 329.5Lx41Wx46H(mm)
 Bolt: 29.5(length)*17.8(diameter)(mm)
 Voltage: DC12V(DC24V need order)
 Start Current: 5.0A
 Standby Current: 0.6A
 Feature: Fail safe(A); Fail secure(B)
 Suitable for: Steel gates; Heavy door
 Signal output: Lock signal NO/NC/COM
 Material: 304 stainless steel
 Waterproof level: IP-55
 Weight: 1.8kg

