

BUTTON SERIES




NEW

PBK-817B/C-AL(R)

Door Release Button(Stainless steel)


Size: 86Lx50Wx30.4H(mm)
114Lx70Wx36.5H(mm)
Standard structure: Stainless steel panel
Output contact: NO,NC
Current rating: 30VDC/1A
Operating temp: -20~+50°C
Weight: 0.2kg



PBK-818A/B/C

Door Release Button(Stainless steel)

Size: 86Lx50Wx40.1H(mm)
88Lx88Wx40.1H(mm)
114Lx70Wx40.1H(mm)
Current rating: 3A@36VDC Max
Output contact: NO/NC/COM
Mechanical life: 500,000 tested
Standard structure: 304 stainless steel panel with metal button
Back box finish: Stainless steel panel, wire drawing finished
Weight: 0.2kg




NEW

PBK-819A/B

Door Release Button(Stainless steel)

Size: 114Lx70Wx39.2H(mm)
86Lx68Wx39.2H(mm)
Standard structure: Stainless steel
Current rating: 3A@36VDC
Output contact: NO/NC/COM
Operating temp: -20°C ~ +50°C
Operating humidity: 0-95% RH
Panel Material: 304 stainless steel panel with wiredrawing finish
Weight: 0.2kg




NEW

PBK-871(LED)

Push Button For The Disable



Size: 133Lx133xW45(mm)
Input Voltage: 12~24VAC/DC
Current: ≤120mA Current Rating: 2A@30VDC
Output Contact: NO/NC/COM
LED: Mode A or Mode B
A: Red when standby, Green when action
B: Green when standby, Red when action
Operating temp: -20°C~+50°C
Weight: 0.35kg



PBS-820A/B/C/D

Piezoelectric Exit Button(Stainless steel)


Size: 90Lx35Wx20H(mm)
86Lx50Wx20H(mm)
86Lx86Wx20H(mm)
114Lx70Wx20H(mm)
Contact area: <100ohm
Current standby: 20mA
Output contact: NO/COM
Current rating: <1A@12VDC(Max.)
Waterproof level: IP-68
Weight: 0.2kg



PBS-820A/B/C/D(LED)

Piezoelectric Exit Button(Stainless steel)

Size: 90Lx35Wx20H(mm)
86Lx50Wx20H(mm)
86Lx86Wx20H(mm)
114Lx70Wx20H(mm)
Voltage: 12V DC
Current: Standby 20mA
Output Contact: NO/COM
Current Rating: 1A@30VDC 0.5A@125VDC
Waterproof Level: IP-65
LED Status: Red: Standby Green: Operation
Weight: 0.18kg



PBS-821A/B(LED)

Piezoelectric Exit Button

Size: 114Lx70Wx16H(mm)
86Lx86Wx16H(mm)
Voltage: 12-24V
Current: Standby 20mA, Operation: 60mA
Output Contact: NO/COM
Current Rating: 1A@30VDC 0.5A@125VDC
Waterproof Level: IP-65
LED Status: Red: Standby Green: Operation
Weight: 0.1kg

